

FTAHQ-4 **Stored pressure fire extinguisher**



FIRE TIPS®
 Fire Tips Protection Service

FTAHQ-4

Stored pressure fire extinguisher



TECHNICAL DATA

Type	FTAHQ-4
Working pressure	15 Bar
Burst pressure	60 Bar
Article	Stored Pressure Fire Extinguisher
Color coding	Blue
PP powder coating	Pure Polyester
Capacity	4 kg
Agent Type	ABC / Powder Map 50%
CE valve	M14
UGTS pressure	Guage
Propellant	Nitrogen
Fire rating	2A:55B
Temperature range	-30°C to 60°C
Discharge time	Min 18 sec
Jet range	Min 3.5 Mtr
Hose / nozzle	EPDM Hose
PVC Black Base	140 mm
Gross Weight	approx. 6.7 kg
Height	approx. 490 mm
Diameter	approx. 140 mm
Mild steel sheet Thickness	approx. 1.6 mm
Approved	BIS / CE

M30 brass valve assembly

Measured by filling up

cylinder 0-15 bar $\pm$ 5%

Tolerance on dimensions

and weight $\pm$ 0.5%

Freeze resistant down to -30°C

Mounting Wall Bracket



FIRE TIPS®
Fire Tips Protection Service